

<b>TECHNICAL SPECIFICATIONS</b>	<b>BARDOLINE PRO S 125 DESIGN</b>
<b>STANDARD</b>	EN 544 4 X 2
<b>WEIGHT OF THE FIBERGLASS</b>	125 g/m <sup>2</sup>
<b>ADHESIVE STRIP</b>	<b>SELF - ADHESIVE BACK SURFACE</b>
<b>WIDTH</b>	337 mm
<b>LENGTH</b>	1000 mm
<b>TENSILE STRENGTH (LONGITUDINAL)</b>	1000 N/5 cm (av.)
<b>TENSILE STRENGTH (TRANSVERSAL)</b>	600 N/5 cm (av.)
<b>TEAR RESISTANCE (TRANSVERSAL)</b>	150 N/5 cm (av.)
<b>WEIGHT</b>	9 kg/m <sup>2</sup>
<b>BUNDLE NET COVERAGE AREA</b>	3,45 m <sup>2</sup>
<b>PALETTE NET COVERAGE AREA</b>	179,40 m <sup>2</sup>
<b>PACKING</b>	<b>MICROPERFORATED PE FOIL</b>
<b>SHEETS PER BUNDLE</b>	24
<b>BUNDLE PER PALETTE</b>	52
<b>BUNDLE WEIGHT</b>	31,05 kg.
<b>PALLET WEIGHT</b>	1614,60 kg.
<b>PALLET DIMENSION</b>	cm 105 x 136 x 110 h

Application shall be carried out when the air temperature is 5°C or higher !