

<b>TECHNICAL SPECIFICATIONS</b>	<b>BARDOLINE PRO TRADITIONAL</b>
<b>STANDARD</b>	EN 544 4 X 2
<b>WEIGHT OF THE FIBERGLASS</b>	100 g/m <sup>2</sup>
<b>ADHESIVE STRIP</b>	<b>HOT - MELT ADHESIVE</b>
<b>WIDTH</b>	340 ±3 mm
<b>LENGTH</b>	1000 ±3 mm
<b>TENSILE STRENGTH (LONGITUDINAL)</b>	700 N/5 cm (av.)
<b>TENSILE STRENGTH (TRANSVERSAL)</b>	450 N/5 cm (av.)
<b>TEAR RESISTANCE (TRANSVERSAL)</b>	100 N (av.)
<b>WEIGHT</b>	10,5 kg./m <sup>2</sup>
<b>BUNDLE NET COVERAGE AREA</b>	3,05 m <sup>2</sup>
<b>PALETTE NET COVERAGE AREA</b>	158,60 m <sup>2</sup>
<b>PACKING</b>	<b>MICROPERFORATED PE FOIL</b>
<b>SHEETS PER BUNDLE</b>	21
<b>BUNDLE PER PALETTE</b>	52
<b>BUNDLE WEIGHT</b>	32,025 kg
<b>PALLET WEIGHT</b>	1665,30 kg
<b>PALLET DIMENSION</b>	cm 105 x 136 x 110 h

Application shall be carried out when the air temperature is 5°C or higher !